Gu, Ray

From: Gu, Ray

Sent: Friday, April 23, 2021 10:33 AM

To: Jon O'Hare Cc: Bou, William

6698208-DM-004 801 3rd Ave Subject:

Hi Jon,

The first round SDOT shoring review is conducted and comments provided below:

- 1. The Geotechnical Engineer shall review the shoring design and indicate whether the relevant recommendations in the Geotechnical Report are implemented and the design is acceptable. Provide a signed and stamped letter from the geotechnical engineer for updated design recommendations and construction considerations, as appropriate
- 2. Indicate the depth of court yar deck with reference to 3rd Ave sidewalk and double check the soil later pressure profile in Calcs.
- 3. On page 2 of plan set, modify the note for yellow deck to: Floor slabs at court and on-grade levels and their columns can be demolished only after rubble is in place at both and north and east walls.
- 4. Provide an optical monitoring program for potential ground movement during construction. It should include at least include three optical survey points at 3rd Ave and one at Marion St
- 5. It is advised to pour CDF to fill the potential gaps or voids between rubble and subsurface walls.

Regards,



Ray Gu, PE, SE Senior Civil Engineer Street Use Division City of Seattle **Department of Transportation**

O: 206.684.5281 | F: 206.684.3130 | ray.gu@seattle.gov

